



SPECIFICATIONS:

1. CONNECTOR JST XHP-2
2. BLACK OR WHITE INSULATED WIRE, 22AWG, MIN.150MM LENGTH AND 5MM STRIPPED
3. RED INSULATED WIRE, 22AWG, MIN. 150MM LENGTH AND 5MM STRIPPED
4. CONNECTOR JST XHP-3
5. HIGH VOLTAGE ACCORDINGLY INSULATED WIRE, RED, BLACK OR WHITE, MIN. 200MM LENGTH
6. TWO (2) COLD CATHODE FLORESCENT LAMP "U" SHAPE
 - 150MM X 5MM X 150MM
 - TUBE DIA=5.0MM
 - UV OUTPUT MIN. 5mW/cm² @ GLASS LEVEL.
 - STARTING VOLTAGE 450V, MAINTAINING VOLTAGE 300V
 - CURRENT 5mA
 - LAMP LIFE: MIN. 5000 HR.
 - DISCHARGE STABILIZATION TIME: 3 MINUTES
7. 12VDC DUAL INVERTER

CAUTION: DO NOT POWER THE INVERTER UNTIL YOU CHECK POLARITY!

Rexim LLC	
SCALE: none	DRAWN BY: VS
DATE: 11/19/2012	APPROVED BY: RS
MCC-UV254-150x10x150 Dual Lamp Inverter Kit	
DIMENSIONS: mm	DN: RX-111912