



SPECIFICATIONS:

1. CONNECTOR JST XHP-2
2. BLACK INSULATED WIRE MIN.150MM LENGTH AND STRIPPED
3. RED INSULATED WIRE MIN. 150MM LENGTH AND STRIPPED
4. CONNECTOR JST XHP-3
5. HIGH VOLTAGE INSULATED WHITE WIRE MIN. 200MM LENGTH
6. TWO (2) UV-185nm COLD CATHODE FLORESCENT LAMP U-SHAPE
 - 150MM X 10MM X 150MM
 - TUBE DIA=5.0MM
 - UV OUTPUT MAX: 4.9 μW/cm² @ GLASS LEVEL.
 - STARTING VOLTAGE 550V, MAINTAINING VOLTAGE 500V
 - CURRENT 5mA
 - LAMP LIFE: MIN. 5000 HR.
 - DISCHARGE STABILIZATION TIME: 3 MINUTES
7. 12V DC - DUAL INVERTER

CAUTION: This inverter is not protected for reverse polarity!
Do not power this inverter until you check polarity.

Rexim LLC	
SCALE: none	DRAWN BY: VS
DATE: 5/05/2020	APPROVED BY: RS
MCC-UV185nm 150x10x150 mm Dual Lamp Inverter Kit	
DIMENSIONS: mm	DRW: RX-10282B