



**SPECIFICATIONS:**

1. CONNECTOR JST XHP-2
2. BLACK INSULATED WIRE MIN.150MM LENGTH AND STRIPPED
3. RED INSULATED WIRE MIN. 150MM LENGTH AND STRIPPED
4. CONNECTOR JST XHP-3
5. HIGH VOLTAGE INSULATED WHITE WIRE MIN. 200MM LENGTH
6. TWO (2) UV-254nm COLD CATHODE FLORESCENT LAMP U-SHAPE
  - 150MM X 10MM X 150MM
  - TUBE DIA=5.0MM
  - UV OUTPUT MAX: 5.0 MW/cm<sup>2</sup> @ GLASS LEVEL.
  - STARTING VOLTAGE 550V, MAINTAINING VOLTAGE 500V
  - CURRENT 5MA
  - LAMP LIFE: MIN. 5000 HR.
  - DISCHARGE STABILIZATION TIME: 3 MINUTES
7. 12V DC - DUAL INVERTER

**CAUTION: This inverter is not protected for reverse polarity!**  
**Do not power this inverter until you check polarity.**

<b>Rexim LLC</b>	
SCALE: none	DRAWN BY: VS
DATE: 5/05/2020	APPROVED BY: RS
MCC-UV254nm 150x10x150 mm Dual Lamp Inverter Kit	
DIMENSIONS: mm	DRW: RX-10281B